QUADRAT Q3 LED

Direct or Indirect interior wall mount luminaire c/w intergral gear.

Die-cast aluminium body

4.6w, 50000hrs

IP20, CRI80, 3000k

Symmetric, mono directional

Integrated LED gear, stabilized output current 350mA dc

Recessed box mod. 506, for wall mounting the unit in

Product Specification

50000 Rated Average Life	**IP20** Ingress Protection Rating	**240V** Voltage	**2.2KG** Weight	**3000K** CCT
Polished Finish	**LED (PCBA)** Lamp Type	**Symmetric** Beam Distribution	**-15 to 40** Operating Temperature	**Steel (Zinc)** Housing

Item Code	Description	Luminaire Colour	System Power	Exit Lumen
SIDD2021	QUADRAT Q3 LED WALL DIRECT/IND 9.2W 350MA CRI80 3000K CHROME	Chrome	9.2W	480Lm
SIDD2020	QUADRAT Q3 LED WALL DIRECT 4.6W 350MA CRI80 3000K CHROME	Chrome	4.6W	240Lm
SIDD2026	QUADRAT Q3 LED WALL DIR/INDIR 9.2W 350MA CRI80 3000K BLACK	Black	9.2W	480Lm
SIDD2022	QUADRAT Q3 LED WALL DIRECT 4.6W 350MA CRI80 3000K ROUGH WHT	White	4.6W	240Lm
SIDD2023	QUADRAT Q3 LED WALL DIRECT 4.6W 350MA CRI80 3000K BLACK	Black	4.6W	240Lm
SIDD2024	QUADRAT Q3 4.6W LED WALL DIRECT 350MA CRI80 3000K BROWN	Brown	4.6W	240Lm
SIDD2025	QUADRAT Q3 LED WALL DIR/IND 9.2W 350MA CRI80 3000K ROUGH WHT	White	9.2W	480Lm
SIDD2027	QUADRAT Q3 LED WALL DIR/INDIR 9.2W 350MA CRI80 3000K BROWN	Brown	9.2W	480Lm

QUADRAT Q3 LED

LINE DRAWINGS



GLG Lighting the future
www.glg lighting